

# BLAST OFF

Multi-Purpose Cleaner  
 Inks, Coatings, Adhesives, and more.

Removes wet and dry material.

- Water based inks.
- Solvent based inks.
- UV inks.
- Coatings, varnishes, and adhesives.
- Low VOC
- Flashpoint over 200°F

**Blast off** can be diluted with water from 25%-100%. Find the best dilution rate of water to achieve desired results.

## Directions of Use:

**Anilox Manual Wash:** Apply onto anilox using a porous sponge or shop towel. Scrub to remove ink pigments, coatings and residues.

**Ultrasonic, Spray Wash machines, and other:**

Find best dilution rate of water to achieve desired result.

**Parts Manual Wash:** Spray or immerse \*part(s) for 1-25 minutes. Remove parts from the cleaner. Use a plastic or brass brush to gently scrub stubborn contaminants loose. Rinse the parts in water, let air dry, or dry with a shop towel.



\*Note: As with all washes, pre-test for compatibility prior to applying onto any surface, substrate, part or general area.

Specifications	
VOC Content lb / gallon 0	3.8
VOC Content grams / liter	450
Flashpoint	> 200 °F. ASTM D56
Color	Colorless
CA Compliant	No

Available In		
Product #	Size	Case Quantity
523270C	Quart	6
523270D	Gallon	4
523270E	5 Gallon	Each