

ALL STAR HL 200

One Step Fountain Solution With Hydro Lube Additive

All Star HL 200 is the evolution of Allied's industry proven All Star Fount technology. With our Hydro Lube added, it not only reduces the dynamic surface tension to low 30s (flattening out fount/water on non-image areas) it thickens and slows fount/water evaporation from non-image areas allowing plates to stay wet longer to assure fast start ups with little waste. Further more ,helps reduce contaminate build up over all.

Along with our added Hydro Lube, many performance-enhancing ingredients have been incorporated into the formula, prevent problems before they can happen and ensure consistent performance,100% of the time.

- Replace 1 or 2 part fount and alcohol subs
- Excellent wetting and viscosity building properties, reduces surface tension to the low 30's
- Razor sharp reverses, cleaner screens, improved ink taping, denser solids
- Suitable for all offset inks including UV / EB
- Compatible with all metal plates, conventional, CTP and non-metal laser plates

Direction For Use:

Recommended dosage range - 3 oz.to 5 oz. per gallon.
Conductivity per ounce is 370 micromhos.
We recommend starting with 4 oz./gallon.
Adjusting dosage up or down as needed.

Specifications:

VOC content lb. / gallon	4.0
VOC content grams / liter	481
Flashpoint	None
Color	Colorless
CA. Compliant	Yes



Recommended dosage range 2.5% to 4%.

Conductivity per 1% is 475 micromhos.

We recommend starting with 3%, adjusting dosage up or down as needed.

Available In:

Product Code	Unit	Case Qty.
10654D	1 Gallon (3.785 ltr)	4
10654E	5 Gallons (18.9 ltr)	Each
10654G	55 Gallons (208 ltr)	Each
10654T	275 Gallons (1040 ltr)	Each



VOC COMPLIANT Air Quality Management District Compliant

